INTEGRATED AUTOMATIC TAMPER · FOR MAHLKÖNIG E65S

PUQ PRESS M3

An automatic tamper designed to sit under a Mahlkönig E65S or E65S GBW. The grinder stands on top, so tamping is built into the grinding station without taking extra counter space.



Made by PUQpress
Barendrecht, Netherlands

5–30 kg	1.5 s	5	147 mm
adjustable tamping pressure	tamping cycle	tamping profiles	high, sits under the grinder

Figures from PUQ's integrated user manual. Height is the tamper unit alone, without grinder.

WHAT IT DOES WELL

01
Grinder on top
The E65S stands on the M3, so the dose is ground and tamped in one place and the bench stays clear.

02
Same tamp every time
Every shot gets the set pressure and a level tamp, so results no longer depend on who is on the bar.

03
Five profiles
Speedy, Precision, Soft, Hulk and Single profiles let you tune the tamp to the roast and to how busy service is.

04
Splash rated
PUQ rates the M3 to IPX1 against dripping water, which suits a working espresso bar where spills happen.

05
Bracket option
Add the M3 bracket and the same tamper can sit under Mazzer Super Jolly, Major and Kony grinders.

06
Less strain on staff
Automatic tamping takes hundreds of repetitive presses a day off each barista, which counts on long, busy shifts.

WELL SUITED TO Cafés and espresso bars using a Mahlkönig E65S or E65S GBW that want tamping without losing counter space.

PUQ PRESS M3 — SPECIFICATION

What you need to plan the space, power and fit. We check compatibility with your grinder before you order.

GRINDER COMPATIBILITY	
Direct fit grinders	Mahlkönig E65S · Mahlkönig E65S GBW
With M3 bracket	Mazzer Super Jolly, Major, Kony (see the M Bracket sheet)

TAMPER	
Tamping pressure	5–30 kg, adjustable in 1 kg steps
Tamping cycle	1.5 seconds
Tamping profiles	Speedy, Precision, Soft, Hulk, Single
Tamper diameter	Built in one size from 53 to 58.3 mm, shown on the tag plate
Dimensions (W × D × H)	194 × 283 × 147 mm
Weight	4.6 kg
Ingress protection	IPX1

ELECTRICAL	
Power	76 W · 0.7 A
Standard supply	100–240 V AC, 50–60 Hz, single phase · standard 13 A socket

SIZE & FOOTPRINT



Size	194 × 283 × 147 mm
Weight	4.6 kg

BEFORE IT ARRIVES

- [ ] Standard 13 A socket for the tamper, as well as the grinder's own supply
- [ ] Level counter (within 0.5°) with 194 × 283 mm clear under the grinder
- [ ] Allow 147 mm extra height under the grinder, plus hopper clearance
- [ ] Confirm grinder model and basket diameter at order

SUPPLIED, SET UP AND LOOKED AFTER BY MSS

Selection & set-up

We help you choose the right model for your grinder and workflow, then set it up and commission it on site.

Maintenance & repairs

Planned maintenance and repair support from our own engineers, looked after alongside the rest of your coffee equipment.

Warranty & ongoing support

New equipment comes with a 12-month parts and labour warranty, subject to manufacturer terms. After that, we look after it for as long as you have it.

TALK TO AN ENGINEER

T 01279 452110 E support@modernstandardservice.com W modernstandardservice.com

SCAN TO VIEW THIS TAMPER ONLINE