INTEGRATED AUTOMATIC TAMPER · FOR MAHLKÖNIG E80

PUQ PRESS M5

An automatic tamper designed to sit under the Mahlkönig E80 Supreme. Pairing a high-output grinder with a built-in tamp keeps the busiest station compact and gives every shot the same level tamp.



Made by PUQpress
Barendrecht, Netherlands

5–30 kg	1.5 s	5	147 mm
adjustable tamping pressure	tamping cycle	tamping profiles	high, sits under the grinder

Figures from PUQ's integrated user manual. Height is the tamper unit alone, without grinder.

WHAT IT DOES WELL

01
Grinder on top
The E80 Supreme stands on the M5, so a high-volume grinding station also tamps without needing more bench.

02
Same tamp every time
Every shot is tamped level at the set pressure, so quality holds up when the queue is at its longest.

03
Five profiles
Speedy, Precision, Soft, Hulk and Single profiles let you favour speed at peak times or a slower, firmer tamp.

04
Splash rated
PUQ rates the M5 to IPX1 against dripping water, suited to a busy bar where spills are routine.

05
Bracket option
Add the M5 bracket and the tamper can sit under large Mazzer grinders such as the Robur and Kold.

06
Less strain on staff
Automatic tamping takes hundreds of repetitive presses a day off each barista, which counts on long, busy shifts.

WELL SUITED TO High-volume cafés, coffee chains and busy hospitality bars running a Mahlkönig E80 Supreme.

PUQ PRESS M5 — SPECIFICATION

What you need to plan the space, power and fit. We check compatibility with your grinder before you order.

GRINDER COMPATIBILITY	
Direct fit grinders	Mahlkönig E80 Supreme
With M5 bracket	Mazzer Robur, Kold (see the M Bracket sheet)

TAMPER	
Tamping pressure	5–30 kg, adjustable in 1 kg steps
Tamping cycle	1.5 seconds
Tamping profiles	Speedy, Precision, Soft, Hulk, Single
Tamper diameter	Built in one size from 53 to 58.3 mm, shown on the tag plate
Dimensions (W × D × H)	233 × 338 × 147 mm
Weight	5.5 kg
Ingress protection	IPX1

ELECTRICAL	
Power	76 W · 0.7 A
Standard supply	100–240 V AC, 50–60 Hz, single phase · standard 13 A socket

SIZE & FOOTPRINT



Size	233 × 338 × 147 mm
Weight	5.5 kg

BEFORE IT ARRIVES

- [ ] Standard 13 A socket for the tamper, as well as the grinder's own supply
- [ ] Level counter (within 0.5°) with 233 × 338 mm clear under the grinder
- [ ] Allow 147 mm extra height under the grinder, plus hopper clearance
- [ ] Confirm grinder model and basket diameter at order

SUPPLIED, SET UP AND LOOKED AFTER BY MSS

Selection & set-up

We help you choose the right model for your grinder and workflow, then set it up and commission it on site.

Maintenance & repairs

Planned maintenance and repair support from our own engineers, looked after alongside the rest of your coffee equipment.

Warranty & ongoing support

New equipment comes with a 12-month parts and labour warranty, subject to manufacturer terms. After that, we look after it for as long as you have it.

TALK TO AN ENGINEER

T 01279 452110 E support@modernstandardservice.com W modernstandardservice.com

SCAN TO VIEW THIS TAMPER ONLINE