INTEGRATED AUTOMATIC TAMPER · FOR MYTHOS MY75/MY85

PUQ PRESS M6

An automatic tamper tailored to the Victoria Arduino Mythos MY75 and MY85, including the gravimetric G versions. The grinder sits on top, so the station tamps every dose level without taking more counter.



Made by PUQpress
Barendrecht, Netherlands

5–30 kg	1.5 s	5	139 mm
adjustable tamping pressure	tamping cycle	tamping profiles	high, sits under the grinder

Figures from PUQ's integrated user manual. Height is the tamper unit alone, without grinder.

WHAT IT DOES WELL

01
Grinder on top
The Mythos MY75 or MY85 stands on the M6, so grinding and tamping share one footprint on the bar.

02
Same tamp every time
Each dose is tamped level at the set pressure, so shot quality no longer depends on who is working.

03
Five profiles
Speedy, Precision, Soft, Hulk and Single profiles let you tune the tamp to the coffee and to service speed.

04
Splash rated
PUQ rates the M6 to IPX1 against dripping water, which suits the area under a working grinder.

05
Uniplate option
With the M6 Uniplate fitted, the tamper can also sit under Anfim SP II and Scody II grinders.

06
Less strain on staff
Automatic tamping takes hundreds of repetitive presses a day off each barista, which counts on long, busy shifts.

WELL SUITED TO Busy cafés and multi-site operators standardising on Victoria Arduino Mythos MY75 or MY85 grinders.

PUQ PRESS M6 — SPECIFICATION

What you need to plan the space, power and fit. We check compatibility with your grinder before you order.

GRINDER COMPATIBILITY	
Direct fit grinders	Victoria Arduino MY75, MYG75, MY85, MYG85
With M6 Uniplate	Anfim SP II, Scody II (see the Uniplate sheet)

TAMPER	
Tamping pressure	5–30 kg, adjustable in 1 kg steps
Tamping cycle	1.5 seconds
Tamping profiles	Speedy, Precision, Soft, Hulk, Single
Tamper diameter	Built in one size from 53 to 58.3 mm, shown on the tag plate
Dimensions (W × D × H)	195 × 381 × 139 mm
Weight	5.2 kg
Ingress protection	IPX1

ELECTRICAL	
Power	76 W · 0.7 A
Standard supply	100–240 V AC, 50–60 Hz, single phase · standard 13 A socket

SIZE & FOOTPRINT



Size	195 × 381 × 139 mm
Weight	5.2 kg

BEFORE IT ARRIVES

- [ ] Standard 13 A socket for the tamper, as well as the grinder's own supply
- [ ] Level counter (within 0.5°) with 195 × 381 mm clear under the grinder
- [ ] Allow 139 mm extra height under the grinder, plus hopper clearance
- [ ] Confirm grinder model and basket diameter at order

SUPPLIED, SET UP AND LOOKED AFTER BY MSS

Selection & set-up

We help you choose the right model for your grinder and workflow, then set it up and commission it on site.

Maintenance & repairs

Planned maintenance and repair support from our own engineers, looked after alongside the rest of your coffee equipment.

Warranty & ongoing support

New equipment comes with a 12-month parts and labour warranty, subject to manufacturer terms. After that, we look after it for as long as you have it.

TALK TO AN ENGINEER

T 01279 452110 **E** support@modernstandardservice.com **W** modernstandardservice.com

SCAN TO VIEW THIS TAMPER ONLINE