STAND-ALONE AUTOMATIC TAMPER · ENTRY LEVEL

PUQ PRESS MINI

PUQ's smallest automatic tamper. It gives a level, repeatable tamp at a set pressure on every shot, in a footprint small enough for tight bars, kiosks and secondary coffee points.



Made by PUQpress
Barendrecht, Netherlands

10–30 kg	1.5 s	3	7 kg
adjustable tamping pressure	tamping cycle	tamping profiles	coffee per week, rated capacity

Figures published by PUQ (Barista Technology B.V.). Capacity is PUQ's weekly coffee rating.

WHAT IT DOES WELL

01
Same tamp every time
The motor applies the set pressure and a flat, level tamp on every shot, so extraction stops varying between baristas and shifts.

02
Small footprint
At 136 mm across it is the narrowest PUQ, which makes it practical beside a compact grinder or on a crowded back bar.

03
Three profiles
Speedy, Precision and Single profiles let you trade a quicker cycle against a more deliberate tamp to suit the coffee and the queue.

04
Pressure in 1 kg steps
Pressure is set anywhere from 10 to 30 kg in 1 kg increments, so a recipe can be locked in and repeated.

05
Spouted or bottomless
Works with single and double spouted portafilters as well as bottomless ones, within the tamper diameter the unit is built for.

06
Less strain on staff
Taking hand tamping out of the routine removes a repetitive wrist and shoulder load from long shifts on the bar.

WELL SUITED TO Smaller cafés, kiosks, offices and hospitality sites serving espresso at low to moderate volume.

PUQ PRESS MINI — SPECIFICATION

What you need to plan the space, power and fit. We check compatibility with your grinder before you order.

TAMPER		
	Tamping pressure	10–30 kg, adjustable in 1 kg steps
	Tamping cycle	1.5 seconds
	Tamping profiles	Speedy, Precision, Single
	Tamper diameter	Built in one size from 53 to 58.3 mm, shown on the tag plate
	Portafilters	Single or double spouted, and bottomless
	Rated capacity	Up to 7 kg of coffee per week
	Dimensions (W × D × H)	136 × 186 × 273 mm
KG	Weight	3.4 kg

ELECTRICAL		
	Power	76 W
	Standard supply	100–240 V AC, 50–60 Hz, single phase · standard 13 A socket

INSTALLATION		
	Max. inclination	0.5°, so the counter must be level

SIZE & FOOTPRINT



Size	136 × 186 × 273 mm
Weight	3.4 kg

BEFORE IT ARRIVES

- [ ] Standard 13 A socket within reach of the grinder station
- [ ] Level counter (within 0.5°) with a 136 × 186 mm footprint clear
- [ ] At least 273 mm height clear under any shelving
- [ ] Confirm your portafilter basket diameter so the right tamper is fitted

SUPPLIED, SET UP AND LOOKED AFTER BY MSS

Selection & set-up

We help you choose the right model for your grinder and workflow, then set it up and commission it on site.

Maintenance & repairs

Planned maintenance and repair support from our own engineers, looked after alongside the rest of your coffee equipment.

Warranty & ongoing support

New equipment comes with a 12-month parts and labour warranty, subject to manufacturer terms. After that, we look after it for as long as you have it.

TALK TO AN ENGINEER

T 01279 452110 **E** support@modernstandardservice.com **W** modernstandardservice.com

SCAN TO VIEW THIS TAMPER ONLINE