STAND-ALONE AUTOMATIC TAMPER · MID VOLUME

PUQ PRESS Q

PUQ's core stand-alone tamper and the model most cafés start with. It delivers a level tamp at a set pressure every time, with five profiles and an adjustment wheel to suit different portafilters.

Made by PUQpress
Barendrecht, Netherlands

5–30 kg	1.5 s	5	25 kg
adjustable tamping pressure	tamping cycle	tamping profiles	coffee per week, rated capacity

Figures published by PUQ (Barista Technology B.V.). Capacity is PUQ's weekly coffee rating.

WHAT IT DOES WELL

01
Same tamp every time
Every shot gets the set pressure and a flat, level tamp, so dose preparation stops being a variable between baristas.

02
Five profiles
Speedy, Precision, Soft, Hulk and Single profiles let you tune the tamp to the roast and to how busy the bar is.

03
Wide pressure range
Pressure is set from 5 to 30 kg in 1 kg steps, so light and dark roasts can each have their own recipe.

04
Adjustment wheel
The adjustment wheel lets the unit be set up for different portafilters, so it suits the handles already on your machine.

05
Spouted or bottomless
Takes single and double spouted portafilters and bottomless ones, within the tamper diameter the unit is supplied with.

06
Less strain on staff
Automatic tamping removes hundreds of repetitive presses a day from each barista, which matters on long, busy shifts.

WELL SUITED TO Independent cafés, restaurants, hotels and workplace coffee bars running steady mid-volume espresso service.

PUQ PRESS Q — SPECIFICATION

What you need to plan the space, power and fit. We check compatibility with your grinder before you order.

TAMPER		
	Tamping pressure	5–30 kg, adjustable in 1 kg steps
	Tamping cycle	1.5 seconds
	Tamping profiles	Speedy, Precision, Soft, Hulk, Single
	Tamper diameter	Built in one size from 53 to 58.3 mm, shown on the tag plate
	Portafilters	Single or double spouted, and bottomless · adjustment wheel
	Rated capacity	Up to 25 kg of coffee per week
	Dimensions (W × D × H)	141 × 195 × 286 mm
KG	Weight	3.5 kg
ELECTRICAL		
	Power	76 W
	Standard supply	100–240 V AC, 50–60 Hz, single phase · standard 13 A socket
INSTALLATION		
	Max. inclination	0.5°, so the counter must be level

BEFORE IT ARRIVES

- [ ] Standard 13 A socket within reach of the grinder station
- [ ] Level counter (within 0.5°) with a 141 × 195 mm footprint clear
- [ ] At least 286 mm height clear under any shelving
- [ ] Confirm your portafilter basket diameter so the right tamper is fitted

SUPPLIED, SET UP AND LOOKED AFTER BY MSS

Selection & set-up

We help you choose the right model for your grinder and workflow, then set it up and commission it on site.

Maintenance & repairs

Planned maintenance and repair support from our own engineers, looked after alongside the rest of your coffee equipment.

Warranty & ongoing support

New equipment comes with a 12-month parts and labour warranty, subject to manufacturer terms. After that, we look after it for as long as you have it.

TALK TO AN ENGINEER

T 01279 452110 **E** support@modernstandardservice.com **W** modernstandardservice.com

SCAN TO VIEW THIS TAMPER ONLINE